

DOOR CLOSER

DHDC-8600



Overview

The aesthetically driven design of DHDC 8600 makes it a top choice for a range of heavy duty applications; aftermarket replacement, aluminum store fronts and new construction.

FITS WHERE YOU NEED IT: The surface mount design and tri pack options' allow you to install this over any high-traffic area while providing complete control.

* Compare to: Norton 8501, LCN 1450, Lawrence LH816, Yale 3301, Corbin-Rosswin DC3210, Hager5200, Dorma 8600, Stanley D3551, Arrow 5016N.

Size: - 1-6 adjustable

Certifications:

- BHMA Certified ANSI A156.4, adjustable sizes 1-6
- ADA Compliant ANSI A117.1 Accessibility Code
- UL/cUL Listed for up to 3 hours
- UL10C Positive Pressure Rated
- UL10B Neutral Pressure Rated
- 30-year Warranty

Material:

- Aluminum Alloy
- The recommended temperatures for prolonged closer use is between -40° F (-42° C) and 150° F (66° C)

Cover:

- Full plastic cover - Standard
- Slim line plastic cover - Optional
- Full size plated metal cover - Optional

Springs:

- Double heat treated steel, tempered springs
- Precision machined, heat treated steel piston

Valves:

- Adjustable latching and sweep speed valves
- Adjustable backcheck valve - Standard
- Delayed action valve - Optional
- Staked valves - Standard

Handing: - Non-Handed

Arms & Brackets:

- Tri-Pack - Regular, parallel arm, and top jamb mount - Standard
- 15% power adjustment in standard arm for regular and top jamb mount

Optional Arms:

- Hold Open Arm
- Extra Heavy Duty Hold Open Stop Arm
- Extra Heavy Duty Stop Arm
- Extra Heavy Duty Arm
- Extra Heavy Duty Hold Open Arm
- Extra Heavy Duty Cushion Stop Arm
- Extra Heavy Duty Hold Open Cushion Stop Arm

DOOR CLOSER

DHDC-8600

DH

Fasteners: - Self-reaming, self-tapping wood and machine screws
- Sex nuts and bolts

Door Thickness: - 1-3/4" (44 mm)
- 1-3/8" - 2-1/4" (36 mm - 57 mm) - Optional

Finishes: - ALM, BLK, BRZ, DBZ, GOL
- Rust inhibiting primer - Standard

Notes: - Used on doors with a maximum weight of 330 lbs.

CUTAWAY VIEW

